



ST504



Features

- Modular zone design
- Double skin insulated stainless steel construction
- Fully adjustable steam lances
- 'Clear view' access doors for viewing inside tunnel
- Excess steam regulated by butterfly valves and variable speed extraction fan

Graham | Sleeveit - Modular Zoned Steam Tunnel

The fully adjustable steam lance system can accommodate multiple lances in each zone, which enables precise and repeatable set up for even the most complex shaped products. The modular approach gives the flexibility to adjust the required length of tunnel to suit the most demanding applications and additional zones can be added after initial installation if and when required.

Each zone is provided with front and rear full-width 'clear view' access doors for a glimpse inside the tunnel. Steam distribution and metering in each zone is provided by easy-to-read numerical indicators enabling the operator to set and repeat the optimum temperature profile for each product allowing for ideal set up of the shrink process and minimum steam usage.

To fully evaluate your product shrinking requirements, samples of containers and sleeve material are essential. Accraply offers a pre order test on your products so you can see the results we can obtain, and can also supply detailed pre sales documentation to assist in creating the perfect sleeve shrink solution.

The Graham | Sleeveit ST504 steam shrink sleeve tunnel is one of the Accraply range of Sleeveit and Label Applicators, Electric and Steam Shrink Systems and container handling devices which form part of the widest range of sleeving systems available in the market. It can be supplied as part of a full sleeving system with an integral conveyor, or as a single item for incorporation into an existing conveyor.



Tunnel Type:	Steam
Conveyor Height min/max:	900 mm/1000 mm [35.43 inch/39.37 inch]
Container Height min/max:	50 mm/300 mm [1.97 inch/11.81 inch]
Container Diameter min/max:	20 mm/150 mm [.79 inch/5.91 inch]
Nozzles	Variable
Pressure:	5 Bar [72.52 PSI]
Electrical:	230 VAC, 1 Phase, 7.5 Amps
Weight:	250kg [550lbs]
Steam Requirements:	150kg steam per hour



** All specification and tooling requirements are subject to Accraply evaluation of all label and product samples. Specifications shown reflect standard machine capabilities. Accraply can also meet other specification requirements. Please call for details.*

Accraply

Trine

Stanford

Graham

Sleeveit

Harland

BW Packaging Solutions consist of Accraply, BW Container Systems, Design Group, Paper Converting Machine Company, Pneumatic Scale Angelus, Thiele Technologies and Synerlink. Through their diverse capabilities, these companies can collectively provide everything from a single piece of equipment to fully integrated, tailor-made packaging line solutions for a wide range of industries, including: food and beverage, personal care, container manufacturing, pharmaceutical and medical devices, household products, paper products and textiles, industrial and automotive, and converting, printing and publishing.

BWPackagingSolutions.com

