

SR_x Serialization Ready Labeling Module



Accraply answers the FDA DSCSA (Drug Supply Chain Security Act) mandate* with the SR_x serialization ready, self-contained label applicator.

This module fully incorporates labeling, printing, vision inspection and rejection on one platform.

The SR_x system is compatible with a variety of labeling systems - not only Accraply models - and is designed to interface with laser and thermal transfer printers and vision systems. By working parallel to your existing conveyor and product handling systems, its compact footprint saves valuable floor space. This roll-up system eliminates the need to reconfigure your packaging line, saving costly downtime and extra expense from revalidation.

SRx Serialization Ready Labeling Module

Features & Benefits

- **Label Quarantine:** Streamline the reconciliation process. The SRx removes failed label from liner and traps it in a separate roll, preventing the rejected label from being used while creating an easily accessed sequence of failed labels ready for reconciliation.
- **Validation of module only:** Module design stands up to validation on its own, saving time and expense.
- **Faster application speed on rounds and panels:** The high dispense speed of the SRx compensates for the longer dwell time when laser printing incremental 2D barcodes (vs. hot stamp).
- **Servo indexing push/pull drive:** Extreme label stop accuracy for printing and inspection within a small capture window.
- **Pedestal style, multi-axis applicator head mount with odometer style positioning gauges:** Ensures repeatable label setups.
- **Vision & printer systems mounting and interface:** Repeatable tool-less positioning of camera and printer.
- **Recipe storage:** Repeatable job setups save time and promote accuracy.
- **Stainless steel main electrical enclosure:** NEMA 12 standards
- **Tool-less changeovers**
- **Accraply partners with industry leaders in laser coding and vision inspection**

Label Staging Accuracy	±1/64" (.4 mm)
Electrical Requirements	230VAC, 3PH, 60Hz, 20A
Air Requirements	80 PSI, 1 CFM
Label Capacity	Maximum Width: 4" (101.6 mm) Minimum Width: 0.5" (12.7 mm) Roll Size-O.D.: 16-20" (406.4 - 508 mm) Core Size-I.D.: 3" (76.2 mm) or 6" (152.4 mm)

Accraply's Gold Standard of Service

"We commit to deliver the highest level of customer care driven by our passion to provide the best customer experience in everything we do."

**Product identification:*

Manufacturers and repackagers must put a unique product identifier on certain prescription drug packages, for example, using a bar code that can be easily read electronically.

Accraply | Trine | Stanford | Graham & Steevit | Harland

Accraply

9350 W Broadway Avenue, Suite 190
Minneapolis, MN 55445 USA

+1 (763) 557-1313
accraply.com

